

ENVIRONMENTAL PRODUCT DECLARATION

In accordance with ISO 14025 and EN 15804:2012+A2:2019 for:



Version 1 Date of publication: 2023/09/05 Validity: 5 years Valid until: 2028/09/05 Scope of the EPD[®]: Romania



Romania production plant

Weber, Saint-Gobain, Turda, county Cluj 22nd December 1989, No.23, 401113 Weber, Saint-Gobain, Stroiesti, county Suceava DN17, Km 4, 727500

Weber, Saint-Gobain, Branesti, county Ilfov I.C. Bratianu, No.284, 077030





THE INTERNATIONAL EPD® SYSTEM

Registration number The International EPD[®] System: **S-P-10311**





General information

Company information

Manufacturer: Saint Gobain Construction Product Romania, WEBER

Saint-Gobain designs, manufactures and distributes materials and services for the construction and industrial markets.

Its integrated solutions for the renovation of public and private buildings, light construction and the decarbonization of construction and industry are developed through a continuous innovation process and provide sustainability and performance.

With 10,000 people and an industrial presence in 60 countries, with 200 production units, WEBER is a global leader in mortar-based solutions.

WEBER is our brand that is committed to building better for people and the planet, offering solutions with performance results that contribute to sustainable development.

At Weber, we design, manufacture and trade solutions for facades, tiling/ flooring, waterproofing, masonry mortars, plastering and plaster-based glazes, silicone sealants.

In Romania, WEBER has 3 production sites:

- 1st from 2002, in Turda, Cluj region West Romania
- 2nd from 2007, on Branesti, Ilfov region South Romania
- 3rd from 2013 on Suceava, Suceava region East Romania

Production plant: Romania, all 3 sites

Management system - related certifications: ISO 9001, ISO 14001

Programme used: EN 15804:2012+A2:2019 Sustainability of construction works – Environmental product declaration - core rules for the product category of construction product and The International EPD® System

PCR identification: (C-PCR) TO PCR 2019:14 Version 1.3.0, date 2023-06-20 c-PCR-003 Concrete and concrete elements

Prepared by: IVL Swedich Environemental Research Institute, EPD International Secretariat

UN CPC CODE : 375

Owner of the declaration: Saint Gobain Construction Product Romania, WEBER Business Unit **Product name and manufacturer represented:** This EPD describes the environmental impact of weberset marmo plus

EPD[®] **prepared by:** Ana-Maria Dumitru (<u>ana-maria.dumitru@saint-gobain.com</u>) and Yves Coquelet (Yves.Coquelet@saint-gobain.com)

Geographical scope of the EPD[®]: Romania

EPD® registration number: S-P-10311

Declaration issued: 2023/09/05, valid until: 2028/09/05

Demonstration of verification: An independent verification of the declaration was made, according to EN ISO 14025:2010. This verification was external and conducted by a third party, based on the PCR mentioned above (see information below).



Programme information

PROGRAMME:	The International EPD [®] System
ADDRESS:	EPD International AB - Box 210 60 - SE-100 31 Stockholm - Sweden
WEBSITE:	www.environdec.com
E-MAIL:	info@environdec.com

CEN standard EN 15804:2012 + A2:2019 serves as the Core Product Category Rules (PCR) **Product category rules (PCR):** PCR 2019:14 Construction Products, version 1.3.0

PCR review was conducted by: The Technical Committee of the International EPD® System **President:** Massimo Marino

Independent third-party verification of the declaration and data, according to ISO 14025:2006: □ EPD process certification ⊠ EPD verification

Third party verifier: Dr Andrew Norton, Director of Renuables Ltd

LCA. Materials. Energy

Tlf +44 (0)7900 560402 - email: a.norton@renuables.co.uk

Approved by: The International EPD© System

Procedure for follow-up of data during EPD validity involves third part verifier:
Yes No

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but from different PROGRAMMEs may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804. For further information about comparability, see EN 15804 and ISO 14025.



Product description

Product description and description of use

The product is an improved deformable white adhesive powder based on mineral binders with reduced slip and extended open-time for walls and floors, indoors and outdoors(C2 TE S1). It is mainly used for gluing marble tiles, composite marble, granite, light colored natural stone, tiles with normal absorption (Class BII, B III), porcelain tiles (Class BI), mosaic and construction materials similar.

All technical characteristics and properties for any product could be find on the website: <u>https://www.ro.weber/placari-ceramice/adezivi-pentru-gresie-faianta-si-piatra-naturala/weberset-marmo-plus</u>

Technical data/physical characteristics:

Technical data/physi	cal characteristics	
Reaction to fire	E	
Initial tensile adhesion strength	≥ 1 N/mm ²	
Tensile adhesion strength after heat ageing	≥ 1 N/mm²	EN12004-2012
Tensile adhesion after water immersion	≥ 1 N/mm ²	EN12004.2012
Tensile adhesion after freeze-thaw cycles	≥ 1 N/mm ²	
Deformability	≥ 2,5 mm & < 5 mm	
Open-time - tensile adhesion strength after 30 min	≥ 0,5 N/mm ²	
Mass of declared unit (kg/m ²)	4.5	



Declaration of the main product components and/or materials

PRODUCT	WEIGHT (KG/M2)	Post-consumer recycled material, weight %	Biogenic material weight kg C/kg
weberset marmo plus	4,5	0	0
PRODUCT COMPONENTS	WEIGHT (%)	Post-consumer recycled material, weight %	Biogenic material weight kg C/kg
White cement	10 – 50 %	0	0
Mineral agregates	30 – 80 %	0	0
Additives	2 – 10 %	0	0
PACKAGING MATERIALS	WEIGHT kg/FU	WEIGHT (%) Vs the product	Biogenic material weight kg C/kg
PE film	0.9978E-04	<0.1%	0
Wooden Pallet	0.1833E-01	<2%	2.70E-04
PE paper bag	0.364E-02	<0.4%	2.00E-04

The product does not contain any hazardous substance listed in the "Candidate List of Substances of Very High Concern (SVHC) for authorization" and "Persistent Bio- accumulative and Toxic (PBT & vPvB)" in a percentage higher than 0.1% by unit weight. The verifier and the PROGRAMME operator do not make any claim nor have any responsibility of the legality of the



LCA calculation information

TYPE OF EPD	Cradle to grave and module D
DECLARED UNIT	4.5 kg/m ²
SYSTEM BOUNDARIES	Mandatory Stages = A1-A3; B1-B7; C1-C4 and D
REFERENCE SERVICE LIFE (RSL)	With minor environmental load is expected to last for the lifetime of the building construction, that is estimated to be 60 years
CUT-OFF RULES	Life Cycle Inventory data for a minimum of 99% of total inflows to the upstream and core module shall be included. Flows related to human activities such as employee transport are excluded. Transportation in-site is excluded. The construction of plants, production equipment and transportation systems are excluded
ALLOCATIONS	Allocation has been avoided when possible. For those cases, when recycled material has been used, a physical allocation based on mass is used. The polluter pays and modularity principles have been followed
GEOGRAPHICAL COVERAGE AND TIME PERIOD	Scope: Romania Data included is collected from 2 production sites in - Romania Production year from 2021
BACKGROUND DATA SOURCE	The databases Gabi 2022 and ecoinvent v.3.8
SOFTWARE	GaBi 10

EPD of construction products may not be comparable if they do not comply with EN 15804. Environmental product declarations within the same product category from different PROGRAMMEs may not be comparable



LCA scope

System bou	tem boundaries (X=included, MND=module not declared)																
	PF	RODU STAGI	CT E	CONS TI ST	STRUC ON AGE			US	SE ST	AGE		END	BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARY				
	Raw material supply	Transport	Manufacturing	Transport	Construction- Installation process	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-recovery
Module	A1	A2	A3	A4	A5	B1	B2	В3	B4	B5	B6	B7	C1	C2	C3	C4	D
Modules declared	х	х	х	x	х	х	х	х	Х	х	х	х	Х	х	х	х	х
Geography	EU	EU	RO	RO	RO	-	-	-	-	-	-	-	ххх	ххх	ххх	ххх	xx
Specific data used		10 %	5 GW	P- GH	G												
Variation products	< 10%																
Variation sites	< 10 %																

System boundaries (X=included. MND=module not declared)

Life cycle stages





A1-A3, Product stage

Description of the stage:

The product stage of the Weber products is subdivided into 3 modules A1, A2 and A3 respectively "Raw material supply", "transport" and "manufacturing". The aggregation of the modules A1, A2 and A3 is a possibility considered by the EN 15804 standard. This rule is applied in this EPD.

Description of the scenarios and other additional technical information:

A1, Raw materials supply

This part takes into account the extraction and processing of all raw materials and energy which occurs upstream to the studied manufacturing process.

Specifically, the raw material supply covers sourcing (quarry) and production of all binder components and additives (e.g. sand, cement, rheology agent and others).

Use of electricity, fuels and auxiliary materials in the production is considered too. The environmental profile of these energy carriers is modeled for local conditions.

A2, Transport to the manufacturer

The raw materials are transported to the manufacturing site. In this case, the modelling includes road and boat transportations (average values) of each raw material.

A3, Manufacturing

This module includes manufacturing of products but also besides on-site activities such as grinding, drying, storing, mixing, packing and internal transportation.

The manufacturing process also collect data on the combustion of refinery products, such as diesel and gasoline, related to the production process.

Packaging-related flows in the production process and all up-stream packaging are included in the manufacturing module, i.e. wooden pallets, paper bag and LDPE film.

Apart from production of packaging material, the supply and transport of packaging material are also considered in the LCA model. They are reported and allocated to the module where the packaging is applied. Data on packaging waste created during this step are then generated. It is assumed that packaging waste generated during production and up-stream processes is 100% collected and either recycled or incinerated with energy recovery.



Manufacturing process flow diagram

Manufacturing process system diagram: Basic scheme of a WEBER Production line



A4-A5, Construction process stage

The construction process is divided into 2 modules:

- A4, transport to the building site and
- A5, installation in the building

A4, Transport to the building site:

This module includes transport from the production gate to the building site. Transport is calculated based on a scenario with the parameters described in the following table.

PARAMETER	VALUE
Fuel type and consumption of vehicle or vehicle type used for transport e.g. long distance truck, boat, etc.	Freight truck trailer <mark>24</mark> t payload, diesel consumption 38 liters for 100 km
Distance	144.6 km
Capacity utilisation (including empty returns)	 100% of the capacity in mass 30% of empty returns
Bulk density of transported products*	1258 kg / m³
Volume capacity utilisation factor	1 (by default)



A5, Installation in the building: this module includes:

In this module was taken into consideration:

- equipment energy used to prepare the product
- 5 % of the material amount estimated to be wasted through excess preparation and cleaning processes, during installation and construction. The losses are considered as landfilled.
- Site-related packaging waste processing is included in the LCA. End-of-life of packaging materials is reported and allocated to the module where it arises.
 For Romania it is applied 249/2015 Rule related to the way to manage packaging and packaging waste – were are set annual minimum % of packaging waste recovery, taking into consideration the total mass.

Not taken into consideration:

- additional accessory for installation
- energy for installation, manual tools are used in this process.

PARAMETER	VALUE (expressed per declared unit)
secondary materials for installation (specified by materials)	none
Water use	1.08 I / FU
Other resource use	None
Quantitative description of energy type (regional mix) and consumption during the installation process	0,0072 MJ/m ²
Wastage of materials on the building site before waste processing, generated by the product's installation (specified by type)	5% losses during installation
Output materials (specified by type) as results of waste processing at the building site e.g. of collection for recycling, for energy recovering, disposal (specified by route)	Paper: 0,11 g/m ² (77.7% recycle, 3.9% recovery, 0% reuse, 59.4% landfill) PE: 0,24E-02 g/m ² (20.8% recycle, 19.7% recovery, 0% reuse, 59.4% landfill) Wooden pallet: 0,70 g/m ² (10.3% recycle, 0.6% recovery, 80% reuse, 9.1% landfill)
Direct emissions to ambient air, soil and water	None

B1-B7, Use stage (excluding potential savings)

The use stage is divided into the following modules:

- B1 Use,
- B2 Maintenance,
- B3 Repair,
- B4 Replacement,
- B5 Refurbishment,
- B6 Operational energy use,
- B7 Operational water use

Once installation is complete, no actions or technical operations are required during the use stages until the end of life stage. The product does not require any energy, water or material input to keep it in working order. Furthermore, is it in contact with the circulating water or the ground. The product covered by this EPD does not require any maintenance as it is aimed for floor leveling. In addition, due to the product durability, maintenance, repair, replacement or restoration are irrelevant in the specified applications. Declared product performances therefore assume a working life that equals the building's lifetime.



For this reason, no environmental loads are attributed to any of the modules between B1 and B5.

C1-C4, End of Life Stage

Description of the stage

The end-of-life stage is divided into the following modules:

C1, Deconstruction, demolition

The de-construction and/or dismantling of the product take part of the demolition of the entire building. 0.05 MJ/m² it is considered to be used for this stage.

C2, Transport to waste processing

This stage includes the transportation effects of demolished waste to a waste processing area. 100 km distance is assumed that the distance between demolishing area to a waste processing area.

C3, Waste processing for reuse, recovery and/or recycling

There is no reuse, recovery or recycling at the end of product life-time. It is assumed that no treatment is needed as 100 % of the material goes to a landfill. No environmental loads are attributed to this stage. It is classified as 'nonhazardous waste' in the European list of waste products.

C4, Disposal

The product is considered to be landfilled at the end of life. The impact of landfill is taken into account according to available data.

Description of the scenarios and additional technical information for the End of life:

PARAMETER	VALUE/DESCRIPTION
Collection process specified by type	4.9 kg/m ² (4,5 kg of dry powder + 0,4 kg of water content) collected with mixed construction waste.
Recovery system specified by type	0% of Waste. There is no recovery, recycling or reuse of the product once it was reached its end of life phase
Disposal specified by type	100 % to municipal landfill
Assumptions for scenario development (e.g. transportation)	Average truck trailer with 27t payload, diesel consumption 38L/100km; 100km distance to landfill

D, Reuse/recovery/recycling potential

100% of wastes are landfilled, so not recycling, recovery or reuse has been considered. Hence, no recycling benefits are reported on stage D.



LCA results

As specified in EN 15804:2012+A2:2019 and also the Product-Category Rules, the environmental impacts are declared and reported using the baseline characterization factors from EC-JRC. Specific data has been supplied by the plant, and generic data come from GABI and Ecoinvent databases.

The estimated impact results are only relative statements which do not indicate the end points of the impact categories, exceeding threshold values, safety margins or risks. All emissions to air, water, and soil, and all materials and energy used have been included.

LCA data results are detailed on the following tables and they refer to a declared unit of 4.5kg/m² weberset marmo plus product.

Description of the system boundary, X = Included in LCA, MND = Module Not Declared



Environmental Impacts

		PRODUCT STAGE	CONSTR ST/		USE STAGE							E	REUSE, RECOVERY RECYCLING			
E	nvironmental indicators	A1/A2/A3	A4 Transport	A5 Installation	B1 Use	B2 Maintenance	B3 Repair	B4 Replacement	B5 Refurbishment	B6 Operational energy use	B7 Operational water use	C1 Deconstruction / demolition	C2 Transport	C3 Waste processing	C4 Disposal	D Reuse, recovery, recycling
	Climate Change [kg CO2 eq.]	1,65E+00	1,24E-02	1,06E-01	0	0	0	0	0	0	0	2,19E-02	2,36E-04	0	2,79E-01	9,50E-05
(Climate Change (fossil) [kg CO2 eq.]	1,65E+00	1,23E-02	9,32E-02	0	0	0	0	0	0	0	2,19E-02	2,37E-04	0	7,42E-02	6,80E-05
	Climate Change (biogenic) [kg CO2 eq.]	3,75E-03	-1,70E-05	1,30E-02	0	0	0	0	0	0	0	2,86E-05	-2,33E- 06	0	2,04E-01	2,57E-05
	Climate Change (land use change) [kg CO2 eq.]	6,17E-04	6,85E-05	6,88E-05	0	0	0	0	0	0	0	2,82E-07	1,61E-06	0	2,14E-04	1,26E-06
\odot	Ozone depletion [kg CFC-11 eq.]	2,97E-08	7,36E-16	1,67E-09	0	0	0	0	0	0	0	1,31E-15	2,34E-17	0	2,75E-16	1,07E-11
65	Acidification terrestrial and freshwater [Mole of H+ eq.]	3,91E-03	7,55E-05	2,63E-04	0	0	0	0	0	0	0	3,41E-05	1,36E-06	0	5,32E-04	-5,01E-07
	Eutrophication freshwater [kg P eq.]	2,13E-04	1,13E-07	2,18E-05	0	0	0	0	0	0	0	1,27E-08	2,62E-09	0	3,91E-07	-3,72E-07
	Eutrophication freshwater [kg (PO ₄) ³ eq.]	6,95E-05	3,67E-08	7,12E-06	0	0	0	0	0	0	0	4,14E-09	8,52E-10	0	1,27E-07	-1,21E-07
	Eutrophication marine [kg N eq.]	1,17E-03	3,71E-05	7,96E-05	0	0	0	0	0	0	0	1,17E-05	6,62E-07	0	1,37E-04	3,89E-07
	Eutrophication terrestrial [Mole of N eq.]	1,26E-02	4,11E-04	8,41E-04	0	0	0	0	0	0	0	1,29E-04	7,35E-06	0	1,51E-03	-8,05E-07
	Photochemical ozone formation - human health [kg NMVOC eq.]	3,46E-03	6,98E-05	2,24E-04	0	0	0	0	0	0	0	3,55E-05	1,25E-06	0	4,78E-04	-6,10E-07
(Z)	Resource use, mineral and metals [kg Sb eq.] ¹	2,95E-06	1,03E-09	1,81E-07	0	0	0	0	0	0	0	8,75E-10	2,40E-11	0	6,66E-09	2,22E-10
	Resource use, energy carriers [MJ] ¹	1,58E+01	1,64E-01	9,73E-01	0	0	0	0	0	0	0	2,88E-01	3,13E-03	0	9,74E-01	2,24E-04
C	Water deprivation potential [m ³ world equiv.] ¹	2,81E-01	1,10E-04	6,37E-02	0	0	0	0	0	0	0	5,88E-05	2,67E-06	0	7,78E-03	-1,38E-05

¹ The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator



Resources Use

		PRODUCT STAGE	CONSTF ST/				US	SE STAGE END OF LIFE STAGE Image: state							D REUSE, RECOVERY, RECYCLING	
Res	ources Use indicators	A1 / A2 / A3	A4 Transport	A5 Installation	B1 Use	B2 Maintenance	B3 Repair	B4 Replacement	B5 Refurbishment	B6 Operational energy use	B7 Operational water use	C1 Deconstruction / demolition	C2 Transport	C3 Waste processing	C4 Disposal	D Reuse, recovery, recycling
*	Use of renewable primary energy (PERE) [MJ]	2.00E+00	9.34E-03	1.26E-01	0	0	0	0	0	0	0	1.14E-03	2.17E-04	0	1.28E-01	-1.14E-02
*	Primary energy resources used as raw materials (PERM) [MJ]	6.90E-02	0	5.81E-03	0	0	0	0	0	0	0	0	0	0	0	0
*	Total use of renewable primary energy resources (PERT) [MJ]	2.07E+00	9.34E-03	1.31E-01	0	0	0	0	0	0	0	1.14E-03	2.17E-04	0	1.28E-01	-1.14E-02
0	Use of non-renewable primary energy (PENRE) [MJ]	1.58E+01	1.65E-01	9.74E-01	0	0	0	0	0	0	0	2.89E-01	3.14E-03	0	9.74E-01	2.24E-04
0	Non-renewable primary energy resources used as raw materials (PENRM) [MJ]	2.80E+00	0	1.41E-01	0	0	0	0	0	0	0	0	0	0	0	0
0	Total use of non-renewable primary energy resources (PENRT) [MJ]	1.86E+01	1.65E-01	1.11E+00	0	0	0	0	0	0	0	2.89E-01	3.14E-03	0	9.74E-01	2.26E-04
6	Input of secondary material (SM) [kg]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
*	Use of renewable secondary fuels (RSF) [MJ]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
0	Use of non-renewable secondary fuels (NRSF) [MJ]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Ø	Use of net fresh water (FW) [m3]	7.45E-03	1.06E-05	1.53E-03	0	0	0	0	0	0	0	2.13E-06	2.51E-07	0	2.46E-04	-3.22E-07



Waste Category & Output flows

		PRODUCT STAGE	CONSTR ST/				US	E STA	GE			EN	ID OF LIF	E STA	GE	D REUSE, RECOVERY, RECYCLING
	Waste Category & Output Flows	A1 / A2 / A3	A4 Transport	A5 Installation	B1 Use	B2 Maintenance	B3 Repair	B4 Replacement	B5 Refurbishment	B6 Operational	B7 Operational water	C1 Deconstruction / demolition	C2 Transport	C3 Waste processing	C4 Disposal	D Reuse, recovery, recycling
	Hazardous waste disposed (HWD) [kg]	6.25E-10	7.88E- 13	7.81E- 10	0	0	0	0	0	0	0	1.13E-12	1.66E- 14	0	1.48E-08	0
Ø	Non-hazardous waste disposed (NHWD) [kg]	1.22E-01	2.36E- 05	2.51E- 01	0	0	0	0	0	0	0	6.05E-05	5.12E- 07	0	4.90E+00	0
Ŵ	Radioactive waste disposed (RWD) [kg]	3.18E-04	2.03E- 07	1.66E- 05	0	0	0	0	0	0	0	3.22E-07	5.83E- 09	0	1.11E-05	0
6>	Components for re-use (CRU) [kg]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Materials for Recycling (MFR) [kg]	7.28E-03	0	5.97E- 04	0	0	0	0	0	0	0	0	0	0	0	0
6	Material for Energy Recovery (MER) [kg]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
6	Exported electrical energy (EEE) [MJ]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
(3)	Exported thermal energy (EET) [MJ]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0



Additional voluntary indicators from EN 15804 (according to ISO 21930:2017)

	PRODUCT STAGE	CONSTR ST/				U	SE STA	GE			EN	ID OF LI	REUSE, RECOVERY RECYCLING		
Environmental indicators	A1/A2/A3	A4 Transport	A5 Installation	B1 Use	B2 Maintenance	B3 Repair	B4 Replacement	B5 Refurbishment	B6 Operational energy use	B7 Operational water use	C1 Deconstruction / demolition	C2 Transport	C3 Waste processing	C4 Disposal	D Reuse, recovery, recycling
GWP-GHG [kg CO2 eq.] ²	1,65E+00	1,23E-02	9,32E-02	0	0	0	0	0	0	0	2,19E -02	2,37E -04	0	7,42E -02	6,80E-05



² This indicator accounts for all greenhouse gases except biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. As such, the indicator is identical to GWP-total except that the CF for biogenic CO₂ is set to zero.

Information on biogenic carbon content

		PRODUCT STAGE
Biog	enic Carbon Content in kg C	A1 / A2 / A3
9	Biogenic carbon content in product [kg]	4.18E-03
9	Biogenic carbon content in packaging [kg]	1.78E-03

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO2.



LCA interpretation

The following figure refers to a declared unit of 4.5kg/m² product

		Product (A1-A3)	Transport (A4)	Installation (A5)	Use (B)	End-of-life (C)	Total	Recycling
							Environmental impacts of the product	Positive benefits of recycling (D)
Climate Change - total	2.00	1.65					-	
kg CO ₂ equiv/FU	1.50 -						-	
C02	1.00 -	_					_ 2.07	
	0.50 -			0.11		0.30		
	0.00		0.01	0.11	0.00		- Kg CO ₂ equiv/FO	0.00
Non-renewable resources								
consumption [1]	20.00	15.81						
MJ/FU	15.00 -						19.2	
	10.00 -						10.2	
	5.00 -		0.16	0.97	0.00	1.26	MJ/FU	0.00
Energy consumption [2]	0.00						-	
	30.00							
IVIJ/FU	20.00	20.68					_	
	10.00 -						23.5	
	0.00 -		0.17	1.25	0.00	1.39	MI/EU	
	-10.00							-0.01
Water consumption [3]	10.00							
m³/FU	0.01	0.007					-	
	0.01	_		0.003			0.01	
	0.00		0.000	0.002	0.000	0.000	0.01	
	0.00						m³/FU	0.000
Waste production [4]	-0.01 🔟							
	6.00					4.90	-	
Kg/FU	4.00						F 37	
	2.00						5.27	
	2.00	0.12	0.00	0.25	0.00		kg/FU	0.00
	0.00							

[1] This indicator corresponds to the abiotic depletion potential of fossil resources.

[2] This indicator corresponds to the total use of primary energy.

[3] This indicator corresponds to the use of net fresh water.

[4] This indicator corresponds to the sum of hazardous, non-hazardous and radioactive waste disposed.

With the graphic views above, it is possible to assess which steps of the LCA are the most impacting for the chosen indicators

The main environmental impacts of the product life cycle come from extraction and processing of raw materials (A1-A3). The Product stage is responsible for over 55% of the impact for following indicators: Climate Change, Ozone depletion, Acidification terrestrial and freshwater, Eutrophication freshwater, Eutrophication marine, Eutrophication terrestrial, Photochemical ozone formation - human health, Resource use, mineral and metals, Resource use, energy carriers and Water scarcity.



Additional information:

Electricity information

TYPE OF INFORMATION	DESCRIPTION								
Location	Representative of average production in Romania								
Geographical representativeness description	Coal Natural gas Hydro Biofuels and waste Oil Nuclear Wind, solar, etc.	11.00% 30.00% 4.10% 13.10% 30.00% 9.40%							
Reference year	2020								
Type of dataset	Cradle to gate from Gabi database								
Source	European Residual Mixes 2019. Association of Issuing Bodies 2020								
CO_2 emission kg CO_2 eq. / kWh	0,592 kg of CO2 eq /kWh (based on Climate Change (fossil) indicator)								



Data quality

Inventory data quality is judged by geographical, temporal, and technological representativeness. To cover these requirements and to ensure reliable results, first-hand industry data crossed with LCA background datasets were used. The data was collected from internal records and reporting documents from Saint Gobain WEBER, Romania. After evaluating the inventory, according to the defined ranking in the LCA report, the assessment reflects 100% inventory data quality.



Environmental impacts according to EN 15804:2012 + A1

The following tables presents results of *weber marmo plus* according to EN 15804 +A1.

	PRODUCT STAGE	CONSTR STA	UCTION GE	USE STAGE					END OF LIFE STAGE				REUSE, RECOVERY, RECYCLING		
Environmental impacts	A1/A2/A3	A4 Transport	A5 Installation	B1 Use	B2 Maintenance	B3 Repair	B4 Replacement	B5 Refurbishment	B6 Operational energy use	B7 Operational water use	C1 Deconstruction / demolition	C2 Transport	C3 Waste processing	C4 Disposal	D Reuse, recovery, recycling
Global Warming Potential (GWP) [kg CO2eq.]	1.62E+00	1.21E- 02	9.91E -02	0	0	0	0	0	0	0	2.16 E-02	2.34E- 04	0	2.11E- 01	8.85E-05
Ozone depletion (ODP) [kg CFC 11eq.]	2.65E-08	7.77E- 19	1.49E -09	0	0	0	0	0	0	0	9.85 E-19	2.08E- 20	0	3.67E- 16	9.58E-12
Acidification potential (AP) [kg SO2eq.]	3.12E-03	5.14E- 05	2.09E -04	0	0	0	0	0	0	0	2.58 E-05	9.31E- 07	0	4.28E- 04	-4.73E-07
Eutrophication potential (EP) [kg (PO4)3-eq.]	8.22E-04	1.31E- 05	4.98E -05	0	0	0	0	0	0	0	4.19 E-06	2.38E- 07	0	4.82E- 05	1.84E-08
Photochemical ozone creation (POCP) - [kg Ethylene eq.]	3.22E-04	1.82E- 06	2.06E -05	0	0	0	0	0	0	0	2.95 E-06	3.33E- 08	0	7.16E- 05	-7.61E-08
Abiotic depletion potential for non-fossil resources (ADP-elements) [kg Sb eq.]	4.91E-06	1.14E- 09	2.80E -07	0	0	0	0	0	0	0	9.05 E-10	2.66E- 11	0	2.57E- 08	1.54E-10
Abiotic depletion potential for fossil resources (ADP- fossil fuels) [MJ]	1.44E+01	1.64E- 01	8.68E -01	0	0	0	0	0	0	0	2.88 E-01	3.13E- 03	0	9.46E- 01	8.78E-04



References

- 1. EPD International (2021) General Programme Instructions for the International EPD® System. Version 4.0. www.environdec.com.
- 2. The International EPD System PCR 2019:14 version 1.3.0 Construction products
- 3. EN 15804:2012 + A2:2019 Sustainability of construction works Environmental product declarations Core rules for the product category of construction products
- 4. ISO 14 025: environmental labels and declarations type III Environmental Declarations Principles and procedure (2009)
- 5. ISO 14 040: Environmental management Life Cycle Assessment Principles and framework (2006)
- 6. ISO 14 044: Environmental management Life Cycle Assessment Requirements and guidelines (2006)
- 7. ISO 14020:2000 Environmental labels and Declarations General principles
- 8. EN 15978 Sustainability of construction works Assessment of environmental performance of buildings Calculation method
- 9. EN 998-1:2016 Specification for mortar for masonry Rendering and plastering mortar
- 10. FprEN 16757:2016 Sustainability of construction works Environmental product declarations -Product Category Rules for concrete and concrete elements

